

Technical Data Sheet

Page 1 of 2

Properties:

AKEMI® AK-GLOSS is a ready for use care product based on high-quality oils and waxes dissolved in CHC-free solvents. It reactivates colour and shine of the surface, provides a water and dirt repellent effect.

The product is characterized by the following properties:

- easy application
- short evaporation time
- very easy to polish without a machine
- strong and long-lasting colour intensification
- produces a high gloss
- surface becomes dirt and water-repellent
- water vapour permeable
- UV-resistant
- non-yellowing

Application Area:

AKEMI® AK-GLOSS restores the gloss of absorbent finely ground, satin-finished, polished or other smooth stone surfaces of all kinds.

Instructions for use:

Disregarding the processing guidelines can lead to irreparable damage!

1. Thoroughly clean surfaces with AKEMI® Stone Cleaner and let them dry.
2. Apply thinly and evenly to the clean and dry surface with a lint-free cotton cloth. Optimum working temperature 15 - 25°C.
3. After evaporation of the solvent remove excess with a soft and lint-free cloth and polish out.
4. To increase the shine and intensify the colour, several applications can be made.

Special Notes:

- For professional use only.
- Objects which are sensitive to solvents, e.g. various synthetic materials, rubber, lacquered parts) in the working area must be protected.
- Before starting work, it is advisable to create a sample area to assess the appearance of the treated object (colour intensification, degree of shine) and to determine the material consumption with sufficient accuracy.
- Apply AKEMI® AK-GLOSS only thinly, otherwise there is a risk of droplet formation, which can lead to an inhomogeneous appearance on absorbent stones.
- Undesired product on stone surfaces can be removed with AKEMI® Stone Cleaner, AKEMI® Wax Stripper or AKEMI® Oil- and Grease Remover Paste.
- Increases the risk of slipping.
- Not recommended for surfaces in contact with food.
- For proper waste disposal, the container must be completely emptied.
- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.

Technical Data:

Colour:	colourless, clear
Coverage:	up to 35 m ² /liter, depending on the absorbency of the stone
Density:	0.79 g/cm ³

TDS 02.26

Technical Data Sheet

Page 2 of 2

Storage:	If stored in dry and cool condition (5 - 25°C/41 - 77°F) in its closed original container at least 24 months from production.
Health & Safety:	Read Safety Data Sheet before handling or using this product.
Important Notice:	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 02.26